

NEW

STONE CRUSHER

RSM - RSM/HP



from 200 to 360 hp



50 cm



40 cm

THE STONE CRUSHER FOR CHALLENGING TASKS.

The RSM - RSM/HP models are suitable for crushing slabs of rock and stones of up to 50 cm in diameter and at a depth of up to 40 cm. They are compatible with tractors of between 200 and 360 hp, and have a working width up to 200 to 230 cm. The RSM line is recommended for challenging agricultural conversion operations, when the land contains rock and stones of significant dimensions, in order to prepare the field for agricultural use. The wide opening and the counter blade allow large material to be guided towards the rotor, as well as maintaining consistent performance while working the land. The optional rear grill holds back larger materials, releasing matter only when it has reached its optimum granulometry. The steel dosing blade, available on request, ensures even distribution of the crushed material.

STANDARD EQUIPMENT	
Hydraulic rear hood	Side gearboxes with oil cooling system (RSM/HP)
Interchangeable inner antiwear plates in Hardox®	Adjustable Hardox® counter-blade
Enclosed machine body	Penetration skids
Centralized greasing hub	
Inside lateral protection	
Protection chains	
Transmission with side gearbox	
Gearbox with freewheel	
Friction clutches	
PTO shaft with cam clutch	
Bolted-on rotor shafts (in forged steel)	
	OPTIONS
	Bolted grid on rear hood
	Multiple tooth options
	Hydraulic top link
	Dozing blade
	Dozing blades with spring system
	Side gearbox with oil cooling system (RSM)



Structural frame in steel.
Maximum strength and durability in heavy duty operations.



Oil-cooling system for side gears.
Greater efficiency and lifespan (optional for RSM)

Interchangeable Hardox® anti wear plates.
Quick and easy maintenance.



Wide opening.
To efficiently process more material



MAIN OPTIONS



1 Rear hood grill Allows larger material.
To be held back and crushed again for optimum results.



2 Adjustable steel dosing blade.
Perfect distribution of the crushed material.



3 Hydraulic top link.
Precise control over operations.



4 Steel dosing blades with spring system.
Excellent even distribution of material and pre-compaction.

MODEL	Tractor (hp)	PTO (rpm)	Working width (mm)	Total width (mm)	Weight (Kg)	Max shredding diameter (mm)	Max working depth (mm)	No. teeth type G/3 +STC/3/FP+STC/FP	
RSM 200	200	300	1000	2080	2490	5060	500	500	94 +4 + 4
RSM 225	200	300	1000	2370	2730	5490	500	500	106 +4 + 4
RSM/HP 250	300	360	1000	2080	2490	5060	500	500	94 +4 + 4
RSM/HP 250	300	360	1000	2320	2730	5490	500	500	106 +4 + 4

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.