# FORESTRY MULCHERS FOR SKID STEERS

PMM/SSL

## Brush mulcher with hammer/flail rotor for skid steers.

A universal mulcher suitable for mulching saplings bushes, crop residues and grass. Thanks to its "floating system", the mulcher's rotor adheres perfectly to the terrain, ensuring a homogeneous material after mulching. The support roller, larger in comparison to other attachments, guarantees the best performance

even on particularly damp terrain. The machine can be equipped with hammers for mulching material up to 8 cm diameter or grass flail to better respond to the various needs of the customer.



Steel counter-blades helps mulch material into a smaller final size



Attachment plate with self leveling device adapts to all types of terrain



Self cleaning rear roller with integrated skids









### STANDARD EQUIPMENT

| 32/65cc variable manual displacement hydraulic piston motor with relief and anticavitation valve | Se |
|--|----|
| Motor enclosed in the frame  | S  |
| Belt transmission  | W  |
| Hydraulic hoses  | Se |
| Front hood with mechanical adjustment  | A  |
| Adjustable skids   |    |

#### OPTIONS

| Customized setting hydraulic motor | Pos |
|------------------------------------|-----|
| Stronger bearing for back roller   |     |

| MODEL                       | PMM/SSL 175 | PMM/SSL 200 |
|-----------------------------|-------------|-------------|
| Engine (hp)                 | 65-100      | 70-100      |
| Flow rate (L/min)           | 56-125      | 56-125      |
| Pressure (bar)              | 180-250     | 180-250     |
| Working width (mm)          | 1780        | 2020        |
| Total width (mm)            | 2000        | 2180        |
| Weight (kg)                 | 850         | 910         |
| Rotor diameter (mm)         | 440         | 440         |
| Max shredding diameter (mm) | 80          | 80          |
| No. hammers type PMM        | 22          | 24          |
| No. flail type Y/3          | 22          | 24          |

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.



(option)

**Multiple flail** 



Self levelling protection flaps

Supporting service leg

Welded counterblades

Self cleaning rear roller with integrated skids

Attachment plate with self levelling device

ossibillity to have the rotor equipped with PML hammers or Y-flail