STONE CRUSHERS FOR SKID STEERS

STC/SSL

Stone Crushers with fixed teeth for skid steer loaders.

Designed and built for High Flow skid steers. Its compact size makes it the ideal solution for dirt and gravel roads, bike and horse trails, driveways, curbs, landscaping and smaller job sites as well as agricultural land reclamation. The spiral rotor

designed configuration ensures even and highly productive crushing capacity and the Hardox® counter knives allow you to adjust the size of the final product. The rear hydraulic door is used to adjust the amount of material exiting the crushing chamber.



Hydraulic hoses

Adjustable Hardox® counter-blade to effectively control the final product size





External pressure control Gauge



Penetration skids

MAIN OPTIONS



Diverter valve to control hood cylinders to control the opening and closing of the hydraulic door



90-120 hp



Depth 15 cm



STANDARD EQUIPMENT

| Hydraulic piston motor 125cc with relief and anticavitation valve | Hydraulic rear door |
|---|--|
| Safety and anticavitation valve | Working pressure control gauge |
| Enclosed / anti dust machine body | Additional reinforced side plates |
| Motor enclosed in the frame | Protection chains |
| Poly Chain® Belt Transmission | Flat pressed welded steel counter-blades |
| Hydraulic hoses | Adjustable Hardox® counter-blade |
| Adaptor wiring | |
| | |

OPTIONS

Diverter valve

| MODEL | STC/SSL 150 |
|------------------------------|-------------|
| Engine (hp) | 90-120 |
| Requirements Flow (I/min) | 110-150 |
| Pressure (PSI) | 220-350 |
| Working width (mm) | 1590 |
| Overall width (mm) | 1894 |
| Weight (lbs) | 1210 |
| Rotor diameter (mm) | 450 |
| Max. working depth (mm) | 150 |
| No. teeth type STCL/3+C/3/SS | 32+4 |
| | |

 ${\it Data\ refers\ to\ machine\ as\ standard.}\ The\ technical\ data\ in\ this\ catalogue\ may\ be\ altered\ without\ prior\ notice.$



